







MODE D'EMPLOI
INSTALLATION INSTRUCTIONS
BEDIENUNGSANLEITUNG
GEBRUIKSAANWIJZING

ST_PSDIN1230_RANGE_A_120312

ALIMENTATIONS MODULAIRES SUR RAIL DIN
DIN RAIL MODULAR POWER SUPPLIES
MODULARE STROMVERSORGUNGEN
FÜR DIN HUTSCHIENENMONTAGE
ELEKTRISCHE VOEDINGEN OP DIN RAIL

12V / 24V / 48V DC

PSDIN1230-PSDIN1245-PSDIN1260
PSDIN2430-PSDIN2445-PSDIN2460
PSDIN4830-PSDIN4845-PSDIN4860

PSDIN		 → 	puissance nominale rated power Dauerstromentnahme nominale belasting		nombre de modules number of modules Teilungseinheiten modulen aantal			
1230 1245 1260	94 x 88 x 65	100V AC 240V AC	12V DC	30 W 45 W 60 W	2,5 A 3,75 A 5 A	5		
2430 2445 2460			24V DC	30 W 45 W 60 W	1,25 A 1,88 A 2,5 A			
4830 4845 4860			48V DC	30 W 45 W 60 W	0,65 A 1 A 1,25 A			
 -10 - +60° C			 0,3 kg					

Montage sur RAIL DIN EN 50 022 - Isolation classe II - Protections électroniques intégrées - Témoin lumineux
Mounting on DIN RAIL EN 50 022 - Class II isolation - Built-in protections - LED indicator
Montage auf DIN EN 50 022 HUTSCHIENE - Isolationsklasse II - Integrierter elektronischer Schutz - Anzeige LED
Te bevestigen op DIN EN 50 022 RAIL - Isolatie Klasse II - Geïntegreerde elektronische beschermings - Indicatie LED

